

- 1. 22 feet of paving.
- 2. Two-way traffic.

NOTE: API GEOMETRIC CROSS SECTIONS SHALL NOT BE COMBINED WITH STANDARD GEOMETRIC CROSS SECTIONS

- 3. No sidewalk allowed.
- 4. No curbs; gutter only.
- 5. No on-street parking allowed.
- 6. Minimum 4 off—street parking spaces per unit, all or any portion of which can be located in a common parking area.
- 7. 24-foot driveway approach width maximum.
- 8. Use on dead-end street only. Cul-de-sac not needed. (Solid waste pickup only at nearest cross street.)
- 9. Serve 6 housing units maximum (6 units include the two corner lots).
- 10. 20-foot minimum setback from property line to garage when garage door fronts on street.
- 11. Street furniture to be located in 10-foot easement as determined through plan review.
- 12. No storm drain lines allowed in this street if a public street. Utilities allowed in the street only to serve adjacent property (no oversize or transmission lines) if a public street.
- 13. Subject to pipeline installation requirements formula except for sewer line placement.
- 14. May be public street only if serving single-family dwelling and only if legislative body makes required findings pursuant to State law (otherwise private street).
- 15. Planned unit development process required.

REF. & REV. AUG. 2002

CITY OF FRESNO

API-5